



## Pro Performance Synthetic Blend SAE 75W-90 Gear Oil

**Pro Performance Synthetic Blend SAE 75W-90 Gear Oil** is a high performance Synthetic Blend sulfur/phosphorous gear lubricant designed for API Service Classification GL-5. It is formulated with additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust prevention, low pour point, and anti-foaming performance. It may be used in limited slip differentials for top-off only.

**Pro Performance Synthetic Blend SAE 75W-90 Gear Oil** is recommended for use in passenger cars, light duty trucks and sport utility vehicles. Always check owner's manual for proper recommendation.

### Benefits

- Excellent wear protection
- Shear resistant
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection
- Compatible with conventional gear lubricants



**RAINBO OIL COMPANY.**  
*Delivering Performance Every Day*

**1-800-942-4425**  
**[www.rainbolubes.com](http://www.rainbolubes.com)**



## Pro Performance Synthetic Blend SAE 75W-90 Gear Oil

### Typical Characteristics

SAE Viscosity Grade		75W-90
Pour Point Deg F.		-35
Flash Point, COC, °F		400
Viscosity		
@ 40°C, cSt		102.8
@100°C, cSt		15.9
Viscosity Index		166
Gravity, API		30.9
Rust Test, ASTM D665		Pass
Product Code #		
Bulk		14800
Drum		17119
Keg		17118
Pail		17117
12/1 Quart		17101



**RAINBO OIL COMPANY.**  
*Delivering Performance Every Day*

**1-800-942-4425**  
**[www.rainbolubes.com](http://www.rainbolubes.com)**